

THREAT4™

powered by **X**acore

Available with Wireless
Sniper/Finger PTT



WATERPROOF TEMPLE TRANSDUCER

SERIES:
x-65000

FEATURES:

- Dual Bone Conduction Transducers
- Available with wireless finger/sniper PTT
- No Audio Bleed on Receive
- Waterproof to 1m for 31mins
- Compatible with most ballistic helmets
- Available in right or left shooter
- Can be worn with ear plugs

SPECIFICATIONS:

MICROPHONE

- Mounting: Left or Right
- Type: Electret (Commercial Radios)
- Impedance: 2.2k Ohm
- Sensitivity: -49 3dB at 1000Hz
- Type: Dynamic (Military Radios)
- Impedance: 150 Ohm
- Sensitivity: -70 dBV/Pa +/- 5 dB at 1000Hz

PTT

- 2" Body PTT
- Wireless Sniper/
Finger PTT (915MHz) 1:1 pairing

MECHANICAL

- Cable Pull from Temple Pad: 10kgf
- Cable Flex at Temple Pad
(90 degree bending): 5000 cycles min,
300g loading
- Mic Boom Pull: 10kgf
- Mic Boom Flex (90 degree bending):
4000 cycles min, 500g loading

WARRANTY:

- 12-months, manufacturers defect

BONE CONDUCTION SPEAKER

- Impedance:
DC 8.5+-10hm, AC 38+-0hm
- Sensitivity: 125+-4dB
- Input Power: Rated 0.5W Max 1W
- Ruggedness: 0.5W, 48hrs

CABLE

- Diameter: 4.5mm

ENVIRONMENTAL

- Storage Temp: -20C to + 70C
- Operating Temp: -20C to 55C
- Submersion: Headset: IP67, 1m
31mins (not including body PTT on
wireless version). Wireless/Sniper
- PTT: IP67,
1m 31mins. Non-wireless body
- PTT: IP67, 1m 31mins.
- Drop: 10 each axis at 5ft w/o failure
- Vibration: 30 mins each axis sweep
- 14-33Hz @ 2.0mm
- Salt Spray: 24hrs @NaCl 5+-1% PH
- 6.5-7.2 Temp. 33.3-37C
- RoHS

**RADIO COMPATIBILITY: NACRE QUIETPRO / MBITR /
PRC / THREAT4 / EDGE WARRIOR / VIC / LVIS / TOCNET /
USB / COMMERCIAL / /CUSTOM**

www.threat4.com | www.xacore.com

1-888-922-6731